

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)


PCT

(10) International Publication Number
WO 2004/059104 A1

- (51) International Patent Classification⁷: **E04F 15/02**,
15/04 Marek [PL/PL]; ul. Gwiazdzista 11 Moczkowo,
PL-74-320 Barlinek (PL).
- (21) International Application Number:
PCT/PL2003/000147 (74) Agent: **BIEGALA, Teresa**; ul. Bialostocka 28,
PL-71-033 Szczecin (PL).
- (22) International Filing Date:
28 December 2003 (28.12.2003) (81) Designated States (*national*): AT (utility model), AT, BY,
CA, CZ (utility model), CZ, DE (utility model), DE, DK
(utility model), DK, EE (utility model), EE, FI (utility
model), FI, HU, JP, LT, LV, NO, PT, RU, UA, US.
- (25) Filing Language: English
- (26) Publication Language: English (84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (30) Priority Data:
P.358084 31 December 2002 (31.12.2002) PL Published:
— with international search report
— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments
- (71) Applicant (*for all designated States except US*): "BAR-
LINEK" S.A. [PL/PL]; ul. Przemysłowa 1, PL-74-320
Barlinek (PL).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **KONSTANCZAK,**

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLOOR PANEL



(57) Abstract: The floor panel (1) which, at least at two opposite sides, is provided with coupling parts in the form of a tongue (6) at one side and a groove (5) at the opposite side, wherein the coupling parts are provided with mechanical locking elements in the form of a protrusion (7), which is formed at the tongue, and a lip (8) bordering the groove, is distinguishable by that the bearing surface (9) of the lip (8) at the longer arm of the groove (5) is concave on the arc with the first radius (r_1) whose point of engagement is situated at the upper edge of the panel (1) whereas the protrusion (7) of the tongue (6) has in its cross-section the form of a circular sector with the third radius (r_3) which is shorter than the first radius, wherein the lower part of the lip (8) and the lower part of the panel (1) from the side of the circular protrusion (7) have the second bearing surfaces (9') which are inclined in relation to the vertical plane in one direction, at the first acute angle (α).